



# ON 4000

# OMNIDIRECCIONAL



## Powerful Omni Directional Scanner

- Solid Structure
- Sensitive automatic sensor
- Outstanding performance
- 650nm visible laser diode
- Depth of field : 25~280mm
- Scan rate : 1650 lines/sec.
- Interface : RS-232, PS2, USB



# ON 4000

# OMNIDIRECCIONAL

Scan Rate	1650 scans lines/sec (Omni-Mode)
	80 scan lines/sec (Single-Line mode)
Sensor	Laser Diode
Wavelength	650nm±10nm
Minimum Barcode Width	0.127mm (5 mil)
Depth of Field	25mm~280mm
Contrast Ratio	35%
Scan Patten	Dual Mode (Omni-directional reading / Single Scan line Mode)
Interface	Keyboard Wedge / RS-232 / USB
Readable Bar Code Symbologies	UPC/EAN, Code 128, Code 93, Codabar, Interleaved 2 of 5, Code 11, Code 39, MSI/Plessey, RSS-14
Power Input	5VDC ± 25%
Laser Class	IEC 60825-1, EN 60825-1
Compliance	CE, FCC
Shock Resistance	1m onto concrete
Weight	140 g (without cable)
Dimension (W x H x L :mm)	79 x 105 x 63.5