



## B-Series Fanless “Cool and Quiet” All-in-One LCD Desktop Touchcomputers

### The Elo TouchSystems B-Series “Cool and Quiet” B2 model

provides a compact, configurable, ruggedized touchcomputer in two screen sizes: 15-inch and 17-inch. These models are available with a choice of three industry-leading Elo touch technologies: IntelliTouch surface acoustic wave, AccuTouch Zero-Bezel resistive and Zero-Bezel APR (Acoustic Pulse Recognition). The “Cool and Quiet” models are fanless—well-suited for environments where noise may be an issue—and can meet the diverse needs of a wide variety of point-of-sale (POS), point-of-information (POI), and point-of-service venues, including retail and hospitality display units, customer loyalty systems, internet access sites, digital signage as well as bedside entertainment, home automation and control.

The B-Series “Cool and Quiet” touchcomputers have a compact, stylish design, with a choice of configuration and connectivity options as well as ease of serviceability. These models feature a fanless Intel Atom™ Dual-Core 1.66GHz processor, and support multiple customer-installable memory and storage configurations.

Also available with the B2 are two fan-cooled B-Series models: the “Performance” B1 touchcomputers with the Intel Celeron Dual-Core 2.2GHz processor; and the powerful “Performance Ultra” B3 touchcomputer with the Intel Core 2 Duo 3.0GHz processors.

### Features

- Small footprint, retail-hardened, flexible touchcomputer
- No-fan model ideal for quiet environments
- Full range of standard connectivity ports plus expansion ports to add functionality
- Customer-installable peripheral, memory and storage options
- Supports industry standard low profile PCI-E (PCI Express) expansion cards
- HDMI output for true high-definition video and audio
- Choice of three industry-leading Elo touch technologies: AccuTouch Zero-Bezel, Zero-Bezel APR (Acoustic Pulse Recognition) and IntelliTouch
- “Designed for touch” from the ground-up; stable stand and tiltable display
- 3 year warranty plus Elo quality and reliability

### Benefits

- Outstanding configurability and customization options to meet all your connectivity needs
- Zero-Bezel models provide a seamless, edge-to-edge design for a sleek appearance that is easy to clean and maintain
- Stability to withstand the rigors of use in a public environment

# B-Series Fanless “Cool and Quiet” All-in-One LCD Desktop Touchcomputers

## Computer Specifications

### 15B2 15-inch model:

### 17B2 17-inch model:

Enclosure color	Dark grey	
Processor	Intel Atom Dual Core D510 1.66GHz 1MB L2 Cache	
Memory (RAM)	1GB DDR2 DIMM on 1 of 2 slots. Expandable to 4GB	
Chipset	Intel NM10 Express	
Video	Intel GMA 3150	
Operating system options	No Operating System; Microsoft Windows 7 Professional (32-bit only); Microsoft Windows POSReady 2009; Microsoft Windows XP Professional Service Pack 3 (32-bit only)	
Serial Ports	2 x RS232	
USB Ports	4 x USB on I/O, 1 x USB Side Access, 1 x USB for Wireless. Additional internal ports available for optional Elo peripherals	
Ethernet Gigabit	1 x LAN RJ45 (Gigabit)	
Audio Ports	1 x 3.5mm line-in; 1 x 3.5mm line-out; 1 x 3.5mm mic-in	
Speakers	Two 2W internal speakers	
Hard Disk Drive	160GB 2.5" SATA HDD	
Real-Time Clock	Replaceable lithium-ion battery for clock	
On-Screen Display (OSD)	Settings: brightness, contrast, phase, auto adjust, H-position, V-position, clock, sharpness, RGB, OSD H-position, OSD V-position, OSD time, OSD language, recall, power button; Languages: English, French, Italian, German, Spanish, Japanese, Traditional Chinese, Simplified Chinese; Lockouts: user controls	
Computer Dimensions (max. with stand, dimensions vary with tilt and options)	14.0" x 10.5" x 14.3" (354.4mm x 267mm x 363.5mm)	15.2" x 10.5" x 14.2" (386.4mm x 267mm x 361.0mm)
Weight	With stand: 19.0lb (8.6kg); without stand: 14.2lb (6.4kg); shipping: 27.6lb (12.5kg)	With stand: 20.5lb (9.3kg); without stand: 15.7lb (7.1kg); shipping: 29.1lb (13.2kg)
Shipping Box Dimensions	17.4" x 10.2" x 21.9" (443mm x 258mm x 555mm)	
Power Consumption (max.)	36W (without peripherals)	
Temperature	Operating: 32°F to 95°F (0°C to 35°C); Storage -4°F to 140°F (-20°C to 60°C)	
Humidity (non-condensing)	Operating: 20% to 80%; Storage: 5% to 95%	
Warranty	3 years	
Backlight Lamp Life	Minimum 50,000 hours to half brightness	
MTBF	50,000 hours demonstrated	
Cables and Accessories	North American and European power cables included	
Power Supply	External 12VDC universal-type power supply brick; AC input voltage: 100-240VAC; Input frequency: 50-60Hz; Max output power: 240W	
Agency Certification	UL/cUL, CE, BSMI, NOM, AR, CCC, EK, KCC, GOST-R, RCM, C-Tick, VCCI	
Other Features	Serviceable internal components; touchscreen sealed to bezel and LCD for APR and AccuTouch models	

## Display Specifications

Display	15.0" diagonal, Active matrix TFT LCD, 4 x 3	17.0" diagonal, Active matrix TFT LCD, 5 x 4
Useful screen area (W x H)	11.97" (304.1mm) x 8.98" (228.1mm)	13.30" (337.9mm) x 10.64" (270.3mm)
Native (optimal) resolution	1024 x 768	1280 x 1024
Colors	16.7 million	
Brightness (typical)	Acoustic Pulse Recognition: 225 nits; AccuTouch: 200 nits; IntelliTouch: 225 nits	
Response time-total (typical)	8 msec	5 msec
Viewing angle (typical)	Horizontal: ±70° or 140° total; Vertical: 60°/65° or 125° total	Horizontal: ±80° or 160° total; Vertical: ±80° or 160° total
Contrast ratio (typical)	700:1	1000:1
Available Touch Technologies	IntelliTouch surface acoustic wave; AccuTouch Zero-Bezel resistive; Zero-Bezel APR (Acoustic Pulse Recognition)	

To find out more about our extensive range of Elo touch solutions, go to [www.elotouch.com](http://www.elotouch.com), or call the office nearest you.

### North America

800-ELO-TOUCH  
Elo Touch Solutions  
Tel 1-650-361-4800  
301 Constitution Drive  
Fax 1-650-361-4722  
Menlo Park, CA 94025-1110  
[customerservice@elotouch.com](mailto:customerservice@elotouch.com)

### Europe

Tel +32 (0)16 35 21 00  
Fax +32 (0)16 35 21 01  
[elosales@elotouch.com](mailto:elosales@elotouch.com)

### Asia-Pacific

Tel +81 (45) 478-2161  
Fax +81 (45) 478-2180  
[www.tps.co.jp](http://www.tps.co.jp)

### Latin America

Tel 786-923-0251  
Fax 305-931-0124  
[www.elotouch.com.ar](http://www.elotouch.com.ar)

Elo Touch Solutions, Inc. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. AccuTouch, Elo (logo), Elo Touch Solutions and IntelliTouch are trademarks of Elo Touch Solutions, Inc. Windows is a trademark of Microsoft Corporation.  
Copyright 2012 Elo Touch Solutions, Inc. All rights reserved. 06/12