



## 1715L 17" LCD Desktop Touchmonitor

**Elo's 1715L touchmonitor** is designed, developed and built to provide a cost-effective touch solution for system integrators, and VARs. It packs Elo's quality and reliability into an integrated, affordable touchmonitor. This new cost- and space-saving touchmonitor is "designed for touch"—the technology is built into the 1715L from the ground up and not added as an afterthought by altering the original monitor. It includes a stable base, controls that are placed on the side rather than the front and are locked-out for public use. The 1715L can function as a desktop or wall-mounted unit and includes a VESA mounting option. The display is factory-sealed against dirt, dust, and liquids, and the unit offers the antiglare clarity and superior performance of Elo's IntelliTouch surface-wave touch technology.

Overall, the 1715L 17" LCD desktop touchmonitor provides a truly economical solution, with Elo's renowned quality. With Elo's portfolio of touchmonitors both first-time and experienced users can now deploy touch solutions to the market more easily and reliably than ever before.

### Features

- "Designed for touch" features such as a stable tilt base
- Long-lasting product cycle
- Available with IntelliTouch Surface Wave Technology, AccuTouch Five-Wire Resistive Technology, or Acoustic Plus Recognition Technology
- Sealed touchscreen
- Dual serial/USB interface
- Removable base and VESA mounting option
- Mounting holes on the base bottom for tabletop security
- Controls on the side, plus lockout function for public use
- Digital on-screen display (OSD)
- Worldwide agency approvals

### Applications

- Point-of-sale (POS)
- Point of service
- Loyalty systems
- Countertop kiosk information systems (KIS)
- Internet access points
- Interactive advertising and display
- Guest check in and check out



# 1715L 17" LCD Desktop Touchmonitor Specifications

## TOUCHMONITOR

Case/Bezel color	Dark gray
Display	Size: 17.0" diagonal Type: Active matrix TFT LCD Aspect ratio: 5 x 4
Useful screen area	Horizontal: 13.3" (338 mm); Vertical: 10.6" (270 mm)
Monitor dimensions	Width: 15.4" (391 mm) Height: (including base) 14.4" (366 mm) Depth: (including base) 8.0" (203 mm)
Optimal (native) resolution	1280 x 1024
Other supported resolutions	1280 x 1024 at 60 or 75 Hz; 1280 x 960 at 60 Hz; 1152 x 864 at 75 Hz; 1024 x 768 at 60, 65 Hz (Sun), 70 or 75 Hz; 832 x 624 at 75 Hz (Mac); 800 x 600 at 56, 60, 72 or 75 Hz; 720 x 400 at 70 Hz; 720 x 350 at 70 Hz; 640 x 480 at 60, 66 Hz (Mac), 72 or 75 Hz
Colors	16.2 million with dithering
Brightness	LCD panel: 280 cd/m <sup>2</sup> (typical) with AccuTouch: 230 cd/m <sup>2</sup> (typical) with Acoustic Pulse Recognition: 258 cd/m <sup>2</sup> (typical) with IntelliTouch: 258 cd/m <sup>2</sup> (typical)
Response time	25 msec (typical)
Viewing angle (from center)	Horizontal (left/right): ±70° or 140° total; Vertical (up/down): 63°/60° or 123° total
Contrast ratio (typical)	450:1
Input video format	RGB analog only
Input sync format	Separate horizontal and vertical sync, composite sync, sync-on-green
Input video signal connector	Mini D-Sub 15-Pin VGA type
Input frequency	Horizontal: 31.5–80 kHz; Vertical: 56.3–75 Hz
Power supply	Type: Internal, with jack to accept power from optional external brick; Monitor input voltage: 100-240 VAC, 50/60 Hz; Optional input voltage: +12VDC ±5%
Power dissipation	50 W max
Temperature	Operating 0°C to 40°C; Storage -20°C to 60°C
Humidity	Operating 20%–80%; Storage 10%–90% noncondensing
Weight (approx.)	Actual: 15.2 lb (6.9 kg); Shipping: 21.2 lb (9.6 kg)
Warranty	Monitor: 3 years Backlight lamp life: typical 40,000 hours to half brightness MTBF: 50,000 hours demonstrated
Agency approvals	UL, cUL, FCC, CE, TÜV-GS, VCCI, IC, C-Tick
On-screen display (OSD)	Digital OSD
User's controls	OSD buttons: menu, up, down, select, power; OSD: contrast, brightness, H/V position, RGB (color temp), clock, phase, recall, language (English, German, Spanish, Japanese, French); OSD disable/enable: power, OSD menu
Mounting options	Threaded-through mounting holes under base, Removable base, 100 mm VESA mount
Other features	Security lock receptacle

To find out more about Elo's extensive range of touch solutions, go to [www.elotouch.com](http://www.elotouch.com), or call the office nearest you.

### North America

Elo TouchSystems  
301 Constitution Drive  
Menlo Park, CA 94025-1110

800-ELO-TOUCH

Tel 1-650-361-4800  
Fax 1-650-361-4722  
[eloinfo@elotouch.com](mailto:eloinfo@elotouch.com)

### Europe

Tel +32 (0)16 35 21 00  
Fax +32 (0)16 35 21 01  
[elosales@elotouch.com](mailto:elosales@elotouch.com)

### Asia-Pacific

Tel +81 (45) 478-2161  
Fax +81 (45) 478-2180  
[www.tps.co.jp](http://www.tps.co.jp)

### Latin America

Tel 786-923-0251  
Fax 305-931-0124  
[www.elotouch.com.ar](http://www.elotouch.com.ar)



Elo TouchSystems reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Elo TouchSystems, IntelliTouch, TE Logo, and Tyco Electronics are trademarks.  
Copyright 2007 Tyco Electronics Corporation ELO-165 11/07

