

MONITOR TOUCH

ON Slim 15"



MONITOR TOUCH ON Slim 15"

Specification

Panel	Cell Type / Glass Surface		TFT LCD / Black Anti-Glare, low reflection coating		
	Aspect Ratio / Size		4 : 3 / 15" viewable diagonal area		
	Active Area / Pixel Pitch		304.13(H) x 228.10(V) mm / 0.297(H) x 0.297(V) mm		
	Native Resolution / Colors		1024(H) x 768(V) / 16.2 Million		
	Brightness / Contrast		250 cd/m2 (typ) / 500 : 1		
	Response Time		≤ 12 ms		
	Viewing Angle (typical)		H. 130° (- 65° ~ + 65°), V. 100° (- 55° ~ + 45°)		
	Light Source		CCFL, Long life, 50,000 hrs (typ)		
Input Sources	PC System	Signal	Analog RGB (0.7/1.0 Vp-p, 75 ohms)		
		Sync	Separate Sync, Composite Sync, Sync On Green		
		Frequency	Fh : 30 - 82Khz , Fv : 50 - 75Hz		
	Audio System	2W speaker x 2			
Input Terminals	1 x VGA (15 Pin Female D-Sub) , 1 x PC Audio (Stereo Headphone Jack), 1 x DC Power Plug				
Convenient Features	Auto Calibration, Back Light Adjustment, Plug&Play (VESA DDC/CI, DDC 2B) OSD Multi-Languages, Wall Mount Ready (VESA 75 x 75 mm)				
Power	External AC-to-12VDC power adapter with universal / Auto-Sensing, AC 90 to 260V, 50 / 60 Hz				
Power Consumption	Operation / Power Saving		20 watt, < 2 watt (Support DPMS)		
Operating Condition	Temperature / Humidity		0°C ~ 50°C (32°F ~ 122°F), 10% ~ 90% (no condensation)		
Storage Condition	Temperature / Humidity		- 20°C ~ 60°C (- 4°F ~ 140°F), 10% ~ 90% (no condensation)		
Certification	FCC, CE				
Dimensions	Physical		With Base(W x H x D) : 359 x 333 x 192 mm		
	Carton		Without Base(W x H x D) : 359 x 299 x 53 mm		
Weight	N.W. / G.W.		4.0 Kgs / 5.0 Kgs		
Container Loaded	20ft / 40ft / 40ft HQ		TBD (Sets, By pallet)		
Touch (Option)	Resolution	Transparency	Linearity	Durability	Driver
Resistive	2048 x 2048	80% ± 3%	X≤1.0%, Y≤1.0%	35 Million Times	MS-OS, Linux, QNX
Capacitive	2048 x 2048	88% ± 2%	XiØ1.0%, Y≤1.0%	200 Million Times	MS-OS, Linux, QNX

